

# POLY-TUF® FEED CARTS

## Price List

Item Number	Maximum Bushel Capacity	Maximum Load Rating*	Overall Size L x W x H	No. of Wheels**	Swivel Tire(s)/ Bearing	Approx. Shipping Weight	Selling Price
<b>(With semi-pneumatic tires)</b>							
<b>P7-4W</b>	7 Bu.	400 lbs.	40 x 22 x 35"	4	8" x 2.50 B.B.	65 lbs.	<b>\$ 327.70</b>
<b>P11-4W</b>	11 Bu.	600 lbs.	44 x 27 x 35"	4	8" x 2.50 B.B.	70 lbs.	<b>355.75</b>
<b>(With air tires — 2-ply tube, recommended for rough, uneven floors and for heavy loads)</b>							
<b>P7A-4W</b>	7 Bu.	400 lbs.	40 x 22 x 35"	4	10" x 3.50 R.B.	70 lbs.	<b>\$406.40</b>
<b>P11A-4W</b>	11 Bu.	600 lbs.	44 x 27 x 35"	4	10" x 3.50 R.B.	77 lbs.	<b>446.90</b>
<b>P14A-4W</b>	14 Bu.	800 lbs.	44 x 32 x 36"	4	10" x 3.50 R.B.	87 lbs.	<b>518.65</b>
<b>P14A-4W-N</b>	14 Bu.	800 lbs.	65 x 27 x 41"	4	10" x 3.50 R.B.	99 lbs.	<b>526.15</b>
<b>P20A-4W</b>	20 Bu.	1000 lbs.	65 x 32 x 41"	4	10" x 3.50 R.B.	104 lbs.	<b>548.50</b>
<b>P26A-4W</b>	26 Bu.	1200 lbs.	72 x 35 41"	4	10" x 3.50 R.B.	119 lbs.	<b>605.25</b>

\* Do not exceed the lower of maximum bushel capacity or load rating (cart's bushel capacity will decrease as lbs. per bushel of material being conveyed increases). Operator should never load cart with more weight than can be safely handled.

\*\* Four-wheel carts are required for use over rough, uneven floors and for moving heavier loads (for greater stability).