

## HAY BALE-ELEVATOR SYSTEMS

### ELECTRIC MOTORS

Item No.	H.P.	R.P.M.	Shaft	Frame Size	Voltage	Approx. Shipping Weight	Selling Price
<b>MT102</b>	1/2	1725	5/8"	56	115/230	25 lbs.	<b>\$ 196.00</b>
<b>MT103</b>	3/4	1725	5/8"	56	115/230	29 lbs.	<b>220.00</b>
<b>MT104</b>	1	1725	5/8"	56	115/230	34 lbs.	<b>252.00</b>
<b>MT105</b>	1-1/2	1725	5/8"	56 H	115/230	46 lbs.	<b>306.00</b>
<b>MT106</b>	2	1740	1-1/8"	182 T *	115/230	88 lbs.	<b>500.00</b>

**NOTE:** Above motors all 115/230 voltage

\*Heavier 182 frame (rather than lighter 145 frame) recommended for our elevators — provides better starting performance/longer life.

**WARNING:** Electric motor must be totally enclosed, fan cooled and have a manual reset overload protector. Motor starting, stopping and motor reset controls must be located so that the operator has view of the entire operation. Wiring should be done by a certified electrician in accordance with local and national codes. Covers are required on all lower sections of conveyor located within 7' of floor or working level or within reach of people. Failure to heed could result in personal injury or death.